

Safety Data Sheet

Federal Register Rules and Regulations

Revision date: 01/15/2015 :

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Hook Wash Lubricant
Product code : Hook Wash Lubricant

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : ElectronicsLubricatingSpray

1.3. Details of the supplier of the safety data sheet

Fixyourstitch
160 Willow Way
Sedona, AZ 86336
928-890-4117

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1 H222
Compressed gas H280

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS02

GHS04

Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H222 - Extremely flammable aerosol
H280 - Contains gas under pressure; may explode if heated

Precautionary statements (GHS-US)

: P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Pressurized container: Do not pierce or burn, even after use
P410+P403 - Protect from sunlight. Store in a well-ventilated place
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

2.3. Other hazards

Other hazards not contributing to the classification

: Contains gas under pressure; may explode if heated.

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Aliphatic Petroleum Naptha	(CAS No) 64742-30-9	>= 40-55	Asp. Tox. 1, H304
carbon dioxide, liquefied, under pressure	(CAS No)124-38-9	1 - 5	Compressed gas, H280
Alphatic Hydrocarbon	(CAS No)64742-96-7	>= 40-55	Not classified

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Cough. Assure fresh air breathing. Allow the victim to rest.
First-aid measures after skin contact	Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Direct contact with the eyes is likely to be irritating. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Shortness of breath.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand. Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Aerosol level 3.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No naked lights. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
----------------------	--

Emergency procedures :
: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill.
Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use.
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.
Storage conditions : Keep only in the original container in a cool, well ventilated place away from: Keep container closed when not in use. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place.
Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.
Storage area : Store in a well-ventilated place.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

carbon dioxide, liquefied, under pressure (124-38-9)

USA ACGIH	ACGIH TWA (mg/m³)	9000 mg/m³
USA ACGIH	ACGIH TWA (ppm)	5000 ppm
USA ACGIH	ACGIH STEL (mg/m³)	54000
USA ACGIH	ACGIH STEL (ppm)	30000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	9000 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm

8.2. Exposure controls

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



:
 Hand protection : Wear protective gloves.
 Eye protection : Chemical goggles or safety glasses.
 Respiratory protection : Wear respiratory protection. Wear appropriate mask.
 Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas
 Appearance :
 Color : Colorless to pale yellow liquid.
 Odor : Colorless. light yellow.
 Odor threshold : characteristic.
 pH :
 Relative evaporation rate (butyl acetate=1) : No data available
 Melting point : 0.19
 Freezing point : -58 °C
 Boiling point : No data available
 Flash point : > 180 °C
 Auto-ignition temperature : > 84 °C
 Decomposition temperature : 236 °C
 Flammability (solid, gas) : No data available
 Vapor pressure : No data available
 Relative vapor density at 20 °C : 0.013 kPa
 Relative density : 4.5
 Solubility : 0.8
 Log Pow : Insoluble in water.
 Log Kow : No data available
 Viscosity, kinematic : No data available
 Viscosity, dynamic : 1.92 cSt @40c
 : No data available

Explosive properties :
:
No data available

Oxidizing properties : No data available

Explosive limits No data available

9.2. Other information

Within VOC Limits :

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

: Not classified

Aliphatic Hydrocarbon (64742-96-7)

LD50 oral rat > 19200 mg/kg (Rat)
: Not classified

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classifiedBased on available data, the classification criteria are not met
Carcinogenicity : Not classified
: Not classifiedBased on available data, the classification criteria are not met

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified
: Not classifiedBased on available data, the classification criteria are not met

Specific target organ toxicity (repeated exposure)

:
: Not classified Based on available data, the classification criteria are not met

Aspiration hazard
Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation : Shortness of breath.
Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

carbon dioxide, liquefied, under pressure (124-38-9)

LC50 fish 1 35 mg/l (96 h; Salmogairdneri (Oncorhynchusmykiss); Lethal)
LC50 fish 2 60 - 240 mg/l (12 h; Salmogairdneri (Oncorhynchusmykiss); Lethal)

12.2. Persistence and degradability

Lubricant

Persistence and degradability Not established.

Aliphatic Hydrocarbon (64742-96-7)

Persistence and degradability Readily biodegradable in water. Biodegradable in the soil. Adsorbs into the soil. Photodegradation in the air.

Aliphatic Hydrocarbon (64742-96-7)

Chemical oxygen demand (COD)	2.25 g O ₂ /g substance
ThOD	2.89 g O ₂ /g substance
BOD (% of ThOD)	> % ThOD (5 day(s)) > 0.5

carbon dioxide, liquefied, under pressure (124-38-9)

Persistence and degradability	Biodegradability: not applicable. No (test) data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

Lubricant

Bioaccumulative potential	Not established.
---------------------------	------------------

Aliphatic Hydrocarbon (64742-96-7)

Log Pow	5.24 - 7.18 (QSAR)
Bioaccumulative potential	Not established.

carbon dioxide, liquefied, under pressure (124-38-9)

Log Pow	0.83 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

Aliphatic Hydrocarbon (64742-96-7)

Surface tension	0.033 N/m (20 °C)
-----------------	-------------------

12.5. Other adverse effects

Other information	: Avoid release to the environment.
-------------------	-------------------------------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations. . Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.
Additional information	: Flammable vapors may accumulate in the container.
Ecology - waste materials	: Hazardous waste due to toxicity. Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

	UN1950, Aerosols, 2.1, Limited Quantity
US DOT (ground):	
ICAO/IATA (air):	UN1950, Aerosols, 2.1, Limited Quantity

IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity
 Special Provisions: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

14.2. UN proper shipping name

DOT Proper Shipping Name : Aerosols flammable, (each not exceeding 1 L capacity)
 Department of Transportation (DOT) Hazard Classes : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
 Hazard labels (DOT) : 2.1 - Flammable gas



DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
 DOT Packaging Exceptions (49 CFR 173.xxx) : 306
 DOT Packaging Non Bulk (49 CFR 173.xxx) : None
 DOT Packaging Bulk (49 CFR 173.xxx) : None

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
 DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
 DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

SECTION 15: Regulatory information

15.1. US Federal regulations

Lubricant

SARA Section 311/312 Hazard Classes : Delayed (chronic) health hazard
 Immediate (acute) health hazard
 Fire hazard
 Sudden release of pressure hazard

15.2. International regulations

CANADA

Lubricant

WHMIS Classification : Class B Division 5 - Flammable Aerosol

EU-Regulations

Safety Data Sheet according to Federal Register Rules and Regulations

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC Not classified

15.2.2. National regulations

15.3. US State regulations

No additional information available

SECTION 16: Other information

Indication of changes : Revision - See : *

Other information : None.

Full text of H-phrases: see section 16:

Asp. Tox. 1

Compressed gas

Flam. Aerosol 1

H222

H280

H304

Aspiration hazard Category 1

Gases under pressure Compressed gas

Flammable aerosol Category 1

Extremely flammable aerosol


Contains gas under pressure; may explode if heated

May be fatal if swallowed and enters airways

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard

Physical : 1 Slight Hazard

Personal Protection : B

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.